






The Guardian Snapshot

GUARDIAN CONCRETE SHELTERS

MODEL TYPE	DIMENSIONS	CAPACITY	PRICE
5 x 7 Slope Guardian	5' x 7' x 6' tall	6 person	Guardian Series prices start at \$3,299 <u>Financing Available</u>
6 x 8 Slope Guardian	6' x 8' x 6'2" extra tall	10 person	
Jumbo Guardian	6'8" x 10' x 6'2" extra tall	16 person	

FEATURES OF THE GUARDIAN CONCRETE SHELTERS

- **Ventilation:** 6" vent and 8" wind turbine vent
- **Steps / Ladder:** 5 skid-resistant welded steel steps with handrail
- **Door:**
 - Reinforced steel door and frame meet FEMA 320 and 361 standards and ICC 500 standard
 - The door has a gas spring assist for easy opening
 - The door has a 3-point locking system for max security
- **Color:** Optional decorative finishes are available for any size Guardian model in gray stone or brown rock finish for additional cost
- 10-year manufacturer warranty
- Made in Oklahoma

STRUCTURAL SPECIFICATIONS	INSTALLATION REQUIREMENTS	TESTING SPECIFICATIONS	
<ul style="list-style-type: none"> • Average weight of 14,000 pounds • Min. of 6,000 psi concrete walls and floor reinforced with heavy steel rebar • Shelter walls over 4 in. thick • 2 piece unit with sealer and bolted straps between parts • Once installed top of shelter is 2 to 2-1/2 feet above ground 	<ul style="list-style-type: none"> • Requires 10 ft. horizontal clearance (or more if sharp turns are required) and 14 feet vertical clearance • Approx. 2 hour installation • Storm shelter appearance can be enhanced with landscape timbers, rail road ties, and/or stone 	<ul style="list-style-type: none"> • Designed in accordance of FEMA 320 and 361 and ICC 500 standards • Door has been tested at Texas Tech Wind and Science Institute 	  

Survivor Shelters
17311 Ok-66
Claremore, OK 74017

Give Survivor Shelters a call to find the right shelter for you!

918-341-4672

www.survivorsheltersllc.com