





# LifeSaver Series Snapshot

## LIFESAVER & LIFESAVER Mini CONCRETE SHELTERS

MODEL TYPE	DIMENSIONS	CAPACITY	PRICE
LifeSaver	5' x 7' x 5'9" tall	12 person	LifeSaver & Mini Series prices start at \$3,499 <u>Financing Available</u>
LifeSaver Mini	5' x 4'6" x 5'9" tall	6 person	

### FEATURES OF LIFESAVER & LIFESAVER Mini CONCRETE SHELTERS

- **Ventilation:** 6" vent and 6" wind turbine vent
- **Steps / Ladder:** Easy access concrete molded steps with safety handrail
- **Door:**
  - Reinforced steel door and frame meet FEMA 320 and 361 standards and ICC 500 standard
  - The door has a gas spring assist for easy opening
  - The door has a 3-point locking system for max security
- **Color:** Optional decorative finishes are available for the full-size LifeSaver model in gray stone or brown rock finish for additional cost
- 10-year manufacturer warranty
- Made in Oklahoma

STRUCTURAL SPECIFICATIONS	INSTALLATION REQUIREMENTS	TESTING SPECIFICATIONS	
<ul style="list-style-type: none"> <li>• Average weight of 14,000 pounds</li> <li>• Min. of 6,000 psi concrete walls and floor reinforced with heavy steel rebar welded "cage"</li> <li>• Shelter walls over 4 in. thick</li> <li>• 2 piece unit with waterproof sealer between parts</li> <li>• Once installed top of shelter is 2 to 3 feet above ground</li> </ul>	<ul style="list-style-type: none"> <li>• Requires 10 ft. horizontal clearance (or more if sharp turns are required) and 14 feet vertical clearance</li> <li>• Approx. 2 hour installation</li> <li>• Storm shelter appearance can be enhanced with landscape timbers, rail road ties, and/or stone</li> </ul>	<ul style="list-style-type: none"> <li>• Designed in accordance of FEMA 320 and 361 and ICC 500 standards</li> <li>• Door has been tested at Texas Tech Wind and Science Institute</li> </ul>	  <p>Examples of available decorative finishes</p>